

Tralift TT/TS Electric Hoist

TRALIFT TS hoists are motorized chain hoist are used to lift and transfer loads. The hoist is designed for permanent installation on a jib crane, or on motorized or non-motorized trolley. They are suitable for handling relatively heavy objects while simultaneously reducing the physical effort of the user. The hoist is operated using a push button pendant control. Alternatively, a wireless remote control is available.

- Compact design
- High performance motor for intensive use
- Efficient and high strength internal mechanism
- Low voltage 42 volts control with emergrncy stop
- Upper and lower electrical gearbox limit switch
- Wear resistant overload slip clutch; with asbestos free lining
- Heat treated gears in oil bath
- Available in Single phase and 3 phase
- Wear resistant brake
- Special load chain to DIN 5684, cadmium plated, grade 8 Load hook to DIN 15401
- Motor protection: IP 55
- Motor insulation : F









| | _ | | |
|-------|----|------|---------------|
| Push | ıΤ | rol | ᄓ |
| 1 431 | | . 01 | $I \subset Y$ |

| Model | Cap. (kg) | Speed (m/min) | No. of falls | Single Phase | 3 Phase | Wt. with 3m of chain (kg) |
|---------|--------------|------------------|-----------------|-----------------|------------|---------------------------------|
| TT/250 | 250 | 8 | 1 | • | • | 19 |
| TT/500 | 500 | 4 | 2 | • | • | 22.5 |
| TT/1000 | 1000 | 4 | 2 | | • | 24.5 |
| TS/1600 | 1600 | 8 | 1 | | • | 63 |
| TS/2000 | 2000 | 4 | 4 | | • | 50 |
| TS/2500 | 2500 | 6 | 2 | | • | 78 |
| TS/3200 | 3200 | 4 | 2 | | • | 73 |
| TS/4000 | 4000 | 4 | 2 | | • | 76 |
| TS/5000 | 5000 | 3.2 | 2 | | • | 76 |



Electric Trolley

Chain Trolley