

Tirak™ Electric Wire Rope Hoist

TIRAK™ Wire Rope Hoist Available in Electric, Hydraulic & Pneumatic Version

- **Extremely Reliable :**
Due to its innovative design, conforming to EN 1808, safety requirements on suspended access equipment as per CE directives and IP 65 protection class.
- **Reduced Maintenance :**
Tirak has a duty cycle of 100%, is robust and very easy to handle and to maintain.
- **Complete Safety :**
Integration on a single hoist Tirak has a no. of complementary safety features such as overload detection device, centrifugal brake, electromagnetic motor brake and a manual descent device.
- **Several Models :**
Range varying from 300 to 3,000 kg
Overload protection ($\geq 1,000$ kg)



Model	WLL (kg)	Lifting speed (m/min)	Power (f/VAC/Hz)	Power (kW)	Wire rope (mm)	Wt. (kg)
X300	300	9	3/400/50	0.5	8.3	27
X302		18	3/400/50	0.9	8.3	27
X301		9	1/230/50	0.5	8.3	29
X400	400	9	3/400/50	0.9	8.3	29
X402		18	3/400/50	1.8	8.3	31
X403		9-18	3/400/50	0.9-1.8	8.3	35
X401		9	1/230/50	0.9	8.3	32
X500	500	9	3/400/50	0.9	8.3	40
X501		18	3/400/50	1.8	8.3	43
X502		9-18	3/400/50	0.9-1.8	8.3	47
X503		9	1/230/50	0.9	8.3	49
X800	800	9	3/400/50	1.8	8.3	45
X802		18	3/400/50	3.2	8.3	49
X803		9-18	3/400/50	1.75-3.5	8.3	49
X805		4.5-9	3/400/50	0.8-1.8	8.3	50
X1020	980	9	3/400/50	1.9	9.5	45
X1023		9-18	3/400/50	1.9-3.8	9.5	56
X1025		4.5-9	3/400/50	0.9-1.9	9.5	55
X1026		4.5-18	3/400/50	0.9-3.8	9.5	71
T1020	980	9	3/400/50	1.9	9.5	71
T1023		9-18	3/400/50	1.9-3.8	9.5	85
T1025		4.5-9	3/400/50	0.9-1.8	9.5	84
T1026		4.5-18	3/400/50	1.9-3.8	9.5	94
X1530	1500	9	3/400/50	2.8	10.2	49
X3050	3000	8	3/400/50	3.8	14.3	105
X3052		12	3/400/50	7.5	14.3	117