


## Total Safety - Slogging Wrench

- Reduces looseness and increases the frictions over the screw, thanks to its safety o-ring, doesn't require to be held with hands avoiding injuries with impacts.
- O-ring is easily replaceable and supports temperatures up to 100°C. Replacements are available for each wrench.
- The wrench does not fall out because it is held by the safety lanyard.
- Only one operator is needed for its safe use (avoiding being used by two operators, which is what usually happens).
- Removable shackles for those applications where height is not a risk.



Lanyards & Tool Belts available



Non Sparking also available

### ■ MM

Code	AF (mm)	L (mm)	A (mm)	B (mm)	C (mm)	Wt. (mm)
AD574257	22	155	38	13	08	0.2
AD574267	23	165	42	14	8.5	0.2
AD574277	24	165	42	14	8.5	0.2
AD574287	25	165	42	14	8.5	0.2
AD574297	26	175	46	16	9.5	0.3
AD562957	27	175	46	16	9.5	0.3
AD574307	28	175	46	16	9.5	0.3
AD574317	29	185	50	16	11	0.4
AD562967	30	185	50	16	11	0.4
AD574327	31	185	55	16	11	0.5
AD574337	32	185	55	16	11	0.5
AD574347	33	210	55	18	11	0.5
AD574357	34	210	55	18	11	0.5
AD574367	35	210	60	19	11	0.6
AD574377	36	210	60	19	11	0.6
AD574387	37	220	60	20	12	0.7
AD574397	38	220	60	20	12	0.7
AD574407	41	225	65	20	12	0.7
AD574417	42	225	65	20	12	0.7
AD574427	45	240	75	22	13	1
AD574437	46	240	75	22	13	1
AD574447	47	240	75	22	13	1
AD574457	48	250	80	23	14	1.2
AD574467	50	250	80	23	14	1.2
AD574477	52	250	80	23	14	1.2
AD574487	54	270	85	24	14	1.4
AD574497	55	270	85	24	14	1.4
AD574507	56	270	85	24	14	1.4
AD574517	58	270	90	26	15	1.6
AD574527	59	270	90	26	15	1.6
AD574537	60	270	90	26	15	1.6
AD574547	61	270	90	26	15	1.6
AD574557	62	270	90	26	15	1.6
AD574567	63	300	100	30	16	1.9
AD574577	64	300	100	30	16	1.9
AD562977	65	300	100	30	16	1.9
AD574587	66	300	100	30	16	1.9
AD574597	67	320	110	32	17	2.3
AD574607	68	320	110	32	17	2.3
AD574617	69	320	110	32	17	2.3
AD574627	70	320	110	32	17	2.3
AD574047	71	320	110	32	17	2.3
AD574057	72	320	110	32	17	2.3
AD574067	73	330	115	33	18	2.9
AD574077	74	330	115	33	18	2.9
AD574087	75	330	115	33	18	2.9

### ■ INCH

Code	AF (inch)	L (mm)	A (mm)	B (mm)	C (mm)	Wt. (mm)
AD574657	7/8	155	38	13	08	0.2
AD574667	15/16	165	42	14	9	0.2
AD574677	1	175	46	16	10	0.3
AD574687	1.1/16	175	46	16	10	0.3
AD574697	1.1/18	185	50	16	11	0.3
AD574707	1.3/16	185	50	16	11	0.4
AD574717	1.1/4	185	55	16	11	0.4
AD574727	1.5/16	210	55	18	11	0.5
AD574737	1.3/8	210	60	19	11	0.5
AD574747	1.7/16	210	60	19	11	0.5
AD574757	1.1/2	220	60	20	12	0.7
AD574767	1.9/16	230	65	20	12	0.7
AD574777	1.5/8	230	65	20	12	0.7
AD574787	1.11/16	230	65	20	12	0.7
AD574797	1.3/4	240	75	22	13	1
AD574807	1.13/16	240	75	22	13	1
AD574817	1.7/8	240	75	22	13	1
AD574827	1.15/16	250	80	23	14	1
AD574837	2	250	80	23	14	1
AD574847	2.1/16	270	85	24	14	1.4
AD574857	2.1/8	270	85	24	14	1.4
AD574867	2.3/16	270	85	24	14	1.4
AD574877	2.1/4	270	90	26	15	1.6
AD574887	2.5/16	270	90	26	15	1.6
AD574897	2.3/8	270	90	26	15	1.6
AD574907	2.7/16	270	90	26	15	1.6
AD574917	2.1/2	300	100	28	16	2.3
AD574927	2.9/16	300	100	28	16	2.3
AD574937	2.5/8	300	100	28	16	2.3
AD574947	2.11/16	320	110	32	17	2.5
AD574957	2.3/4	320	110	32	17	2.5

